PATENT

DK-US055008

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Takeshi HIKAWA et al. : Attn.: Application Processing Division

: Customer Correction Branch

Serial No.: 10/521,942

Filed: January 21, 2005

For: DRIVE UNIT FOR COMPRESSOR AND REFRIGERATOR

REQUEST FOR CORRECTION OF OFFICIAL FILING RECEIPT

Assistant Commissioner of Patents Washington, DC 20231

Sir:

Applicants have noticed a U.S. Patent and Trademark Office error in the Title on the Official Filing Receipt. Specifically, the Title was incorrectly typed as

" DRIVER OF COMPRESSOR AND REFRIGERATOR " while it should be

-- DRIVE UNIT FOR COMPRESSOR AND REFGIGERATOR --.

A Preliminary Amendment was filed with the application correcting the Title.

Attached is a copy of the Official Filing Receipt received from the PTO in the above application, with the correction noted thereon. Issuance of a corrected Filing Receipt is respectfully requested.

The correction is not due to Applicant error, therefore, no fee is due.


Respectfully submitted,

David L. Tarnoff Reg. No. 32,383

SHINJYU GLOBAL IP COUNSELORS, LLP 1233 Twentieth Street, NW, Suite 700 Washington, DC 20036 (202)-293-0444

Dated: 8-4-05

G:\08-AUG05-TH\DK-US020802 Request Filing Receipt correction(PCT 見本).doc



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. 1450 Alexandra, Viginia 22313-1450 www.unptu.gov

FILING OR 371 (c) DATE APPL NO. ART UNIT FIL FEE REC'D ATTY.DOCKET NO DRAWINGS TOT CLMS IND CLMS 10/521.942 01/21/2005 3744 1800 **DK-US055008** 12 38 2

CONFIRMATION NO. 3925

FILING RECEIPT

OC000000016508824

Date Mailed: 07/20/2005

Receipt is acknowledged of this regular Patent Application. It will be considered in its order and you will be notified as to the results of the examination. Be sure to provide the U.S. APPLICATION NUMBER, FILING DATE, NAME OF APPLICANT, and TITLE OF INVENTION when inquiring about this application. Fees transmitted by check or draft are subject to collection. Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please mail to the Commissioner for Patents P.O. Box 1450 Alexandria Va 22313-1450. Please provide a copy of this Filing Receipt with the changes noted thereon. If you received a "Notice to File Missing Parts" for this application, please submit any corrections to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections (if appropriate).

Applicant(s)

22919

Takeshi Hikawa, Osaka, JAPAN: Toshiyuki Maeda, Shiga, JAPAN; Shinichi Kasahara, Osaka, JAPAN; Takahiro Yamaguchi, Osaka, JAPAN; Shigenobu Izumi, Shiga, JAPAN; Kiyoshi Koizumi, Osaka, JAPAN; Masanobu Kita, Shiga, JAPAN:

Assignment For Published Patent Application

SHINJYU GLOBAL IP COUNSELORS, LLP

1233 20TH STREET, NW, SUITE 700

WASHINGTON, DC 20036-2680

DAIKIN INDUSTRIES, LTD., OSAKA, JAPAN

Power of Attorney: The patent practitioners associated with Customer Number 22919.

Domestic Priority data as claimed by applicant

This application is a 371 of PCT/JP03/09415 07/24/2003

Foreign Applications

Projected Publication Date: 10/20/2005

Non-Publication Request: No

Early Publication Request: No.

JUL 2 5 2005

Global IP Counselors, LLP

Title

PRIVE UNIT for COMPRESSOR and REFRIGERATOR

Preliminary Class

062

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process simplifies the filing of patent applications on the same invention in member countries, but does not result in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at http://www.uspto.gov/web/offices/pac/doc/general/index.html.

LICENSE FOR FOREIGN FILING UNDER Title 35, United States Code, Section 184 Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.


This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the

national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Office of Export Administration, Department of Commerce (15 CFR 370.10 (j)); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. DOI 1490 Alexandrix, Vinginia 22313-1450 www.uspto.gov

ATTY. DOCKET NO. FIRST NAMED APPLICANT

U.S. APPLICATION NUMBER NO. 10/521.942

Takeshi Hikawa

DK-US055008

INTERNATIONAL APPLICATION NO.

PCT/JP03/09415

22919 SHINJYU GLOBAL IP COUNSELORS, LLP 1233 20TH STREET, NW, SUITE 700 **WASHINGTON, DC 20036-2680**

I.A. FILING DATE PRIORITY DATE

CONFIRMATION NO. 3925 371 ACCEPTANCE LETTER

OC00000016508825

07/24/2003

Date Mailed: 07/20/2005

NOTICE OF ACCEPTANCE OF APPLICATION UNDER 35 U.S.C 371 AND 37 CFR 1.495

The applicant is hereby advised that the United States Patent and Trademark Office in its capacity as a Designated / Elected Office (37 CFR 1.495), has determined that the above identified international application has met the requirements of 35 U.S.C. 371, and is ACCEPTED for national patentability examination in the United States Patent and Trademark Office.

The United States Application Number assigned to the application is shown above and the relevant dates are:

01/21/2005

01/21/2005

DATE OF RECEIPT OF 35 U.S.C. 371(c)(1), (c)(2) and (c)(4) REQUIREMENTS

DATE OF COMPLETION OF ALL 35 U.S.C. 371 REQUIREMENTS

A Filing Receipt (PTO-103X) will be issued for the present application in due course. THE DATE APPEARING ON THE FILING RECEIPT AS THE "FILING DATE" IS THE DATE ON WHICH THE LAST OF THE 35 U.S.C. 371 (c)(1), (c)(2) and (c)(4) REQUIREMENTS HAS BEEN RECEIVED IN THE OFFICE. THIS DATE IS SHOWN ABOVE. The filing date of the above identified application is the international filing date of the international application (Article 11(3) and 35 U.S.C. 363). Once the Filing Receipt has been received, send all correspondence to the Group Art Unit designated thereon.

The following items have been received:

- Copy of the International Application filed on 01/21/2005
- English Translation of the IA filed on 01/21/2005
- Copy of the International Search Report filed on 01/21/2005
- Preliminary Amendments filed on 01/21/2005
- Information Disclosure Statements filed on 01/21/2005
- Oath or Declaration filed on 01/21/2005
- Request for Immediate Examination filed on 01/21/2005
- U.S. Basic National Fees filed on 01/21/2005
- Assignment filed on 01/21/2005
- Priority Documents filed on 01/21/2005
- Power of Attorney filed on 01/21/2005

Applicant is reminded that any communications to the United States Patent and Trademark Office must be mailed to the address given in the heading and include the U.S. application no. shown above (37 CFR 1.5)

DARRELL C COTTMAN
Telephone: (703) 308-9140 EXT 203

PART 1 - ATTORNEY/APPLICANT COPY

FORM PCT/DO/EO/903 (371 Acceptance Notice)

DK-US055008

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Takeshi HIKAWA et al.

Serial No.: New – (National Phase of

PCT/JP2003/009415)

Filed: Herewith

For: DRIVE UNIT FOR COMPRESSOR AND

REFRIGERATOR (AS AMENDED)

PRELIMINARY AMENDMENT

Assistant Commissioner of Patents Washington, DC 20231

Sir:

Prior to examination of the above-identified application, please amend the subject application as follows.

Amendments to the Title begin on page 2 of this paper.

Amendments to the Specification begin on page 3 of this paper.

Amendments to the Abstract begin on page 4 of this paper.

Amendments to the Claims are reflected in the <u>Listing of Claims</u>, which begins on page 5 of this paper. Claims 1-58 are pending, with claims 1 and 6 being the only independent claims.

Remarks/Arguments begin on page 13 of this paper.

Filed: Herewith

AMENDMENTS TO THE TITLE:

Please replace the title of this application with the following rewritten version:

DRIVE UNIT FOR DRIVER OF COMPRESSOR AND REFRIGERATOR

Filed: Herewith

AMENDMENTS TO THE SPECIFICATION:

Please add the following paragraph on page 1, between lines 2 and 3:

CROSS-REFERENCE TO RELATED APPLICATIONS

This nonprovisional application claims priority under 35 U.S.C. §119(a) to Japanese Patent Application No. 2002-216025, filed in Japan on July 25, 2002, and Japanese Patent Application No. 2002-367841, filed in Japan on December 19, 2002, the entire contents of which are hereby incorporated by reference. --

Please replace the heading at page 2, line 26, with the following rewritten version:

SUMMARY OF THE INVENTION DISCLOSURE OF THE INVENTION

Please replace the heading at page 24, line 3, with the following rewritten version:

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS BEST

MODE FOR CARRYING OUT THE INVENTION

Please replace the heading at page 50, line 1, with the following rewritten version:

WHAT IS CLAIMED IS: CLAIMS

Filed: Herewith

AMENDMENTS TO THE ABSTRACT:

Please replace the paragraph (Abstract) beginning at page 58, line 1 with the following rewritten version:

ABSTRACT

An instantaneous current and instantaneous voltage of a three-phase coil (10) of a brushless DC motor (6) are detected, and the internal condition of a compressor (1) is predicted from these detection values. The prediction about the internal condition of the compressor (1) is made in such a way that motor driving torque which is a parameter of a motor model is identified and poor lubrication, liquid compression or the like is predicted from this identified motor driving torque. This enables it to make, in real time, a failure forecast, failure diagnosis etc. on the compressor (1).

Filed: Herewith

The following Listing of Claims will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS:

1. (Currently Amended) A drive unit for a compressor having a motor (6), the drive unit comprising:

<u>a</u> detecting <u>component configured and arranged to detect at least one of means (16, 17) for detecting the <u>a</u> current <u>of said motor</u> and/or <u>a</u> voltage of said motor (6); and</u>

<u>a</u> prediction <u>component configured and arranged to predict means (28) for predicting</u> an internal condition based on detection values obtained by said detecting means (16, 17) <u>component</u>.

2. (Currently Amended) The drive unit for a compressor according to claim 1, wherein

the prediction <u>component</u> means (28) has <u>an</u> identification <u>component</u> means (20) for identifying a parameter of a motor model from the detection values obtained by the detecting <u>component</u> means (16, 17), and <u>a</u> derivation <u>component</u> means (21) for deriving the internal condition based on the parameter identified by said identification <u>component</u> means (20).

3. (Currently Amended) The drive unit for a compressor according to claim 1, wherein

the internal condition predicted by the prediction <u>component</u> means (28) is shaft abnormalities or poor lubrication.

4. (Currently Amended) The drive unit for a compressor according to claim 1, wherein

the internal condition predicted by the prediction $\underline{\text{component}}$ $\underline{\text{means}}$ (28) is motor temperature.

Filed: Herewith

5. (Currently Amended) The drive unit for a compressor according to claim 1, wherein

the motor (6) is a brushless DC motor.

6. (Currently Amended) A refrigerator <u>comprising</u>: having a refrigerant circuit provided with a compressor (1) including a motor; (6), the refrigerator comprising:

a detecting component configured and arranged to detect at least one of means (16, 17) for detecting the a current of said motor and/or a voltage of said motor (6); and a prediction component configured and arranged to predict means (28) for predicting an internal condition of the compressor (1) based on detection values obtained by said detecting means (16, 17) component.

- 7. (Currently Amended) The refrigerator according to claim 6, wherein said prediction component means (28) has an identification component means (20) for identifying a parameter of a motor model from the detection values obtained by the detecting component means (16, 17), and a derivation component means (21) for deriving the internal condition of the compressor (1) based on the parameter identified by the identification component means (20).
 - 8. (Currently Amended) The refrigerator according to claim 6, wherein said motor (6) is a brushless DC motor.
- 9. (Currently Amended) The refrigerator according to claim 7, wherein the parameter identified by said identification component means (20) is motor driving torque.
- 10. (Currently Amended) The refrigerator according to claim 6, wherein the internal condition predicted by said prediction component means (28) is the high refrigerant pressure or low refrigerant pressure of the refrigerant circuit.

Filed: Herewith

11. (Currently Amended) The refrigerator according to claim 9, wherein said refrigerant circuit is provided with <u>a</u> refrigerant detecting means (22, 23) for detecting a refrigerant state, and

wherein said derivation component means (21) derives being configured to derive the high refrigerant pressure or low refrigerant pressure of the refrigerant circuit based on the motor driving torque identified by the identification component means (20) and the refrigerant state detected by the refrigerant detecting component means (22, 23).

12. (Currently Amended) The refrigerator according to claim 9, wherein said refrigerant circuit is provided with the a refrigerant detecting component means (22, 23) for detecting a refrigerant state, and

wherein the derivation means (21) is formed such that the relationship between motor driving torque corresponding to the at least one of a refrigerant temperature and/or a refrigerant pressure of the refrigerant circuit and the degree of suction superheat of the compressor (1) is set beforehand and such that the degree of suction superheat of the compressor (1) is derived based on the motor driving torque identified by the identification means (20) and the refrigerant state detected by the refrigerant detecting component means (22, 23).

- 13. (Currently Amended) The refrigerator according to claim 6, wherein the internal condition predicted by the prediction component means (28) is occurrence of an impact load within the compressor (1).
- 14. (Currently Amended) The refrigerator according to claim 13, wherein the detection value obtained by the detecting component means (16) is the current of the motor (6), and

wherein the prediction <u>component</u> means (28) predicts occurrence of an impact load from the higher harmonic component of the detection current obtained by the detecting <u>component</u> means (16).

Filed: Herewith

15. (Currently Amended) The refrigerator according to claim 14, wherein the prediction component means (28) predicts occurrence of an impact load from the amount of distortion in the sine wave of the higher harmonic component of the detection current.

- 16. (Currently Amended) The refrigerator according to claim 14, wherein the prediction component means (28) predicts occurrence of an impact load when the higher harmonic component of the detection current is greater than a preset reference value.
- 17. (Currently Amended) The refrigerator according to claim 16, wherein the reference value for the prediction component means (28) is set in accordance with at least one of the refrigerant temperature and/or refrigerant pressure of the refrigerant circuit.
- 18. (Currently Amended) The refrigerator according to claim 6, wherein the internal condition predicted by the prediction component means (28) is poor lubrication or liquid compression in the compressor (1).
- 19. (Currently Amended) The refrigerator according to claim 18, wherein the detection value obtained by the detecting component means (16) is the current of the motor (6), and

wherein the prediction component means (28) predicts the poor lubrication or liquid compression of the compressor (1), based on the increasing rate of the detection current obtained by the detecting component means (16).

20. (Currently Amended) The refrigerator according to claim 19, wherein the refrigerant circuit is equipped with a refrigerant detecting component means (22, 23) for detecting a refrigerant state, and

wherein the prediction component means (28) is formed such that a stationary current for the motor (6) in its steady state is set based on the detection current detected by the

Filed: Herewith

detecting <u>component</u> means (16) and based on the refrigerant state detected by the refrigerant detecting <u>component</u> means (22, 23) and such that the poor lubrication or liquid compression of the compressor (1) is predicted by making a comparison between said stationary current and the detection current detected by the detecting <u>component</u> means (16).

- 21. (Currently Amended) The refrigerator according to claim 9, wherein the prediction component means (28) predicts poor lubrication or liquid compression in the compressor (1) based on an increase in motor driving torque which exceeds a specified value.
- 22. (Currently Amended) The refrigerator according to claim 21, wherein the refrigerant circuit is equipped with a refrigerant detecting component means (22, 23) for detecting a refrigerant state, and

wherein the prediction component means (28) is formed such that a stationary torque for the motor (6) in its steady state is set based on the motor driving torque identified by the identification component means (20) and based on the refrigerant state detected by the refrigerant detecting component means (22, 23) and such that the poor lubrication or liquid compression of the compressor (1) is predicted by making a comparison between said stationary torque and the motor driving torque identified by the identification component means (20).

- 23. (Currently Amended) The refrigerator according to claim 9, wherein the prediction component means (28) outputs information on the internal condition of the compressor (1) which has been predicted.
- 24. (Currently Amended) The refrigerator according to claim 9, further comprising:

<u>a</u> protection means (29) for configured and arranged to protecting the compressor (1) based on information on the internal condition of the compressor (1) predicted by the prediction component means (28).

Filed: Herewith

25. (Currently Amended) The refrigerator according to claim 24, wherein the protection component means (29) controls an inverter controlling component means (26) for driving the compressor (1) to perform a protective operation of the compressor (1).

- 26. (Currently Amended) The refrigerator according to claim 25, wherein the protection component means (29) controls the inverter controlling component means (26) to perform the protective operation of the compressor (1) in preference to operation control of the refrigerant circuit.
- 27. (Currently Amended) The refrigerator according to claim 24, further comprising:

<u>a</u> switching <u>component</u> <u>means</u> for switching from the protective operation of the protection <u>component</u> <u>means</u> (29) to a steady operation, based on the information on the internal condition of the compressor (1) which has been predicted by the prediction <u>component means</u> (28).

- 28. (Currently Amended) The refrigerator according to claim 24, wherein the protection component means (29) makes a failure diagnosis on the compressor 1.
- 29. (Currently Amended) The refrigerator according to claim 28, further comprising:

<u>a</u> memory <u>component</u> means (21) for memorizing the result of the diagnosis made by the protection <u>component</u> means (29).

30. (Currently Amended) The refrigerator according to claim 24, wherein the protection component means (29) is so formed as to forecast a failure in the compressor (1).

Filed: Herewith

31. (Currently Amended) The refrigerator according to claim 30, further comprising:

<u>a</u> communication <u>component</u> means (31) for outputting information on the forecast made by the protection <u>component</u> means (29).

- 32. (Currently Amended) The refrigerator according to claim 24, wherein the protection component means (29) is so formed as to alter the control content or control parameter of the refrigerant circuit.
- 33. (Currently Amended) The refrigerator according to claim 6, wherein a refrigerant system model for the refrigerant circuit is provided beforehand, and the operating condition of the refrigerant circuit is predicted based on information on the internal condition of the compressor (1) predicted by the prediction component means (28).
 - 34. (Currently Amended) The refrigerator according to claim 7, wherein the motor (6) is a brushless DC motor, and wherein the prediction component means (28) predicts a motor temperature from the

current and voltage of the motor (6) and instrument constants.

35. (Currently Amended) The refrigerator according to claim 7, wherein the motor (6) is a brushless DC motor,

wherein the identification means (20) identifies a parameter based on a motor model constituted by the current and voltage of the motor (6), resistance and inductance, and

wherein the derivation <u>component</u> means (21) derives motor temperature based on the parameter identified by the identification <u>component</u> means (20).

36. (Currently Amended) The refrigerator according to claim 35, wherein the identification component means (20) obtains a motor voltage equation in such a way that a d-axis is plotted in the direction of the N pole of magnets (1b) of the motor (6), a q-axis is plotted in the direction which is shifted forward from the d-axis by $\pi/2$, and a motor

Filed: Herewith

basic voltage equation for a three-phase PMSM is converted into a d, q axis coordinate system which rotates at an electric angular speed ω , and the identification component means (20) then identifies a magnetic flux characteristic value associated with an armature flux linkage generated by the magnets (1b), using said motor voltage equation, and

wherein the derivation component means (21) derives the temperature of the magnets (1b) as motor temperature based on the magnetic flux characteristic value identified by the identification component means (20).

- 37. (Currently Amended) The refrigerator according to claim 36, wherein the identification component means (20) obtains a voltage equation for a steady state from the motor voltage equation, and at the time of the identification, the d-axis component of the armature current of said steady-state voltage equation is set to zero.
- 38. (Currently Amended) The refrigerator according to claim 35, wherein the refrigerant circuit has <u>a</u> refrigerant detecting <u>component</u> means (24) for detecting the temperature of a discharge pipe of the compressor (1), and

wherein a calibration component means (36) is being configured such that the motor temperature derived by the derivation component means (21) being regarded as the internal temperature of the compressor 1, the internal temperature derived by the derivation component means (21) is calibrated based on the discharge pipe temperature detected by the temperature detecting component means (24).

Filed: Herewith

REMARKS

Entrance of this Amendment is respectfully requested.

Respectfully submitted,

David L. Tarnoff Attorney of Record Reg. No. 32,383

SHINJYU GLOBAL IP COUNSELORS, LLP 1233 Twentieth Street, NW, Suite 700 Washington, D.C. 20036

(202)-293-0444

Dated: 01-21-05

G:\01-JAN05-MSM\DK-US055008 preliminary amendment.doc